

The logo for UNKA SOUND SYSTEMS is centered on a dark, textured background. It features a stylized 'U' and 'K' symbol on the left, followed by the word 'UNKA' in a large, bold, outlined font. Below 'UNKA' is the phrase 'SOUND SYSTEMS' in a smaller, italicized, outlined font. A red brushstroke underline is positioned below the text.

**UNKA**  
*SOUND SYSTEMS*

Unique Audio Solutions



# **FORCE H212A 2.0**

**2 AMPLIFICATION CHANNELS  
INDIVIDUAL AMPLIFICATION  
2x1.050W**

Unique ratio of performance to size  
Self powered

#### APPLICATIONS

Portable AV systems.

Houses of worship: theaters, stadiums, concert halls, arenas,  
tour sound reinforcement.

Large-scale events

#### DESCRIPTION

test at 1 kHz, single channel controlled). With a THD  
1% maximum (EIAJ  $\Omega$  1,050 W at 8Hom.

An integrated Class D amplifier offers 2 outputs  
141 dB SPL. Horizontal use, with exceptional settings  
multi-peak, including vertical magnet woofers and  
neodymium, provided the H212A has two standards  
12 "coaxial, both sound quality and matrix  
SPL. element, which meets the highest average power line,  
Weatherproof, the FORCE H212A speaker is compact,  
self-powered under the Unka quality control system.

Optimization of our systems.

We have created several possibilities to arm our systems, according to the needs  
of our clients.

We are aware that we have clients who need to have absolute control over  
the system and clients who do not need this type of technology.

For this reason we have decided to create 2 FORCE H212 systems ( active and passive)  
considering that their Internal components are always the same, the only difference is  
power and control.

#### FORCE H212A 2.0

It has a 2x1,050w power module, the two channels are used for its own enclosure.

Without external control and with 4 presets.

By installing the DSP-4 you can have external control via network. The possibilities of control  
and management. Total is excellent. Control is done with Harmony



General	
Type	Point source / line array format
Transducers	2x 12" neodymium magnet woofer with 2.5" voice coil 2x compression driver with 2.5" voice coil
Frequency Response	120 Hz – 19 kHz (-6 dB)
Maximum SPL	141 dB (peak)
Coverage	30° horizontal 100° vertical

Internal Amplifier Module	
Type	2-ch., switch mode, class D
Peak Output Power	2x 1050 W @ 8 Ω 1% THD+N <sup>3</sup>
Operating Range	100-240V AC, 50-60 Hz with PFC
Power Consumption	300 W @ 8 Ω load, Pink noise 1/8 rated power
Protections	Over Temp. (Power Limiting – Thermal Shutdown), Short Circuit/Overload Output Protection, Power Limiting, Clip Limiter/Permanent Signal Limiter, High Frequency Protection

Controls and Connectivity		
Connectivity	Analog: 1x XLR (bal) input signal 1x XLR (bal) parallel output	Mains: 1x powerCON 1x powerCON link

Handling	
Dimensions (WxHxD)	700 x 350 x 220 mm (27,55 x 13,78 x 8,66 in)
Weight	34 kg / 75 lb (with rigging hardware)